

File

ALL
3 1/2" W.P.

SPECIFICATIONS
for a
TWO MANUAL AND PEDAL PIPE ORGAN
Designed For
ST. FRANCIS XAVIER CATHEDRAL
GREEN BAY, WISCONSIN

6055

Revised 7-25-85

MANUAL COMPASS C4 TO C4 61 NOTES
PEDAL COMPASS CCC TO G 32 NOTES
CONSOLE Detached - Tilting-tablet - Desk Style
DISPLAY FRONT Expression Enclosure

<u>GREAT</u>		<u>SWELL</u>	
8'	Principal	8'	Gemshorn
8'	Rohrgedeckt	8'	Gemshorn Celeste TC
8'	Gemshorn	8'	Rohrflöte
8'	Gemshorn Celeste TC	4'	Flute
4'	Principal	4'	Gemshorn
4'	Copula	2 2/3'	Quint
2'	Octave	2'	Blockflöte
2'	Gemshorn	1 1/3'	Larigot
III	Mixture	1'	Gemshorn
8'	Trompette	8'	Trompette
4'	Clarion		Tremolo

PEDAL

- 16' Subbass
- 16' Lieblich (soft wind)
- 8' Principal
- 8' Rohrgedeckt
- 4' Choralbass
- 2' Flute
- 16' Contre Trompette
- 4' Clarion

RESOURCES

16'	Rohr Gedeckt	#19-50 [1/2 on 8"]	1/4 97 Pipes	1-18 = WOOD #2 19-24 = ZINC 25-97 = 40% TIN TOP 30 = OPEN TREBLES <i>Black Felt</i>
8'	Principal	45 [1/2 on 18"]	4/15 85 Pipes ZINC + 50/50	
4'	Gemshorn	60 [1/2 on 18"]	4/15 73 Pipes 40% TIN	
8'	Gemshorn Celeste TC		4/15 49 Pipes like Gemshorn 40% TIN	
16'	Trompette	1-12 = A.-S. #4 sc. 13-85 = A.-S. #3 sc.	85 Pipe 1-12 = FR. WIDE 2 16' = All ZINC. Rest = FR. NARROW 5 Rest = ZINC + ORGAN METAL	

COUPLERS

- Swell to Great
- Great to Pedal
- Swell to Pedal

ACCESSORIES

- Expression Pedal
- Crescendo Pedal and Indicator
- Wind Indicator Light
- Music Rack Light
- Pedal Light
- Organ Bench with Music Compartment and Back Rest
- Sforzando Reversible - Thumb and Toe
- Motor Switch
- Blower and Rectifier
- 25 Feet Cable

COMBINATION ACTION

- Six Pistons affecting Great - *Thumb*
- Cancel
- Six Pistons affecting Swell - *Thumb*
- Cancel
- Six Pistons affecting Pedal - *Toe only*
- Cancel
- Ten General Pistons affecting entire organ - *Thumb + Toe*
- General Cancel