

TWO MANUAL AND PEDAL PIPE ORGAN

Designed for  
TUSCOLA METHODIST CHURCH

4732

*Partby*

TUSCOLA, ILLINOIS  
MANUAL COMPASS C C TO C 4 61 NOTES  
PEDAL COMPASS C C C TO G 32 NOTES

SUBMITTED May 7, 1966

CONSOLE Detached Drawknob controls, Style # 6, built to AGO Specifications

DISPLAY FRONT None Required

CHAMBER PREPARATIONS: To be prepared by Purchaser

PITCH: International A - 440

GREAT ORGAN (Unenclosed Non-compressive)	
* 8'	Principal 47 1/4 61 Pipes s.l.or 49
* 8'	Rohrflöte 50 3/4 61 Pipes Half 49
* 4'	Viole (from Swell) 60 1/4 61 Notes
* 4'	Octave 57 1/5 61 Pipes s.l.or 61
* 2'	Spitzflöte 71 3/4 T 1/4 61 Pipes s.l.or 61
* 11	Blockflöte 84-91 1/4-1/4 122 Pipes s.l.or 1-18 22-26 19-40 19-22 45-54 15-19 55-61 12-15
	Forniture 84-91 1/4-1/4
	Chimes (Prepared for)

(To be enclosed in a resonant wood expression chamber, to be provided and erected by organ builder.)

8'	Gedackt cur Nick 61 Pipes wood 49
8'	Viole 58 61 Pipes s.l.or 49
8'	Viole Celeste T. C. 60 49 Pipes Half 61
* 4'	Koppelflöte 61 1/5 61 Pipes Half 61
* 2 2/3'	Nazard 63 3/8 T 1/5 61 Pipes Half 61
* 2'	Principal 70 2/4 61 Pipes 40% tin 61
* 1 3/5'	Terz 72 N. HOEN SS. 2/12-1/16 61 Pipes Half 61
8'	Trompete 82 5/8" FR. 61 Pipes
4'	Trompete 12
	Tremulant

PEDAL ORGAN

16'	Quintbasse 47 32 Pipes 20
8'	Bourdon 48 2/4 32 Pipes Half, wood Bass
4'	Choralbass 58 1/4 32 Pipes s.l.or 32
11 Rk.	Mixture Rauschpfeife 2 3/4 - 2' 64 Pipes 65-71 2/4-1/4
16'	Posaune 5" ENGL. 32 Pipes 64

COUPLERS

Great to Great 4'	Swell Union Off
Swell to Great 4'	Swell to Swell 16'
Swell to Great 8'	Great to Pedal 8'
Swell to Great 16'	Swell to Pedal 4'
Swell to Swell 4'	Swell to Pedal 8'

COMBINATION ACTION

(The Preferred Remote Controlled Capture System, Visible affecting drawknobs.)

Four Pistons affecting Great Stops and Couplers - Thumb

Cancel

Four Pistons affecting Swell Stops and Couplers - Thumb

Cancel

Four Pistons affecting Pedal Stops and Couplers - Toe of Thumb

Cancel

Four General Pistons affecting entire organ Thumb and

duplicated by Toe Studs

General Cancel

Sforzando Piston, affecting entire organ Thumb and Toe

ACCESSORIES

Resonant wood Swell expression chamber with laminated louvers, Organ bench with music storage and back to be provided and erected by organ builder. Separate wind regulators for all chest and

Balanced Swell Expresfor Pedal to Swell enclosure needs, as required for steady air.

Balanced crescendo pedal, adjustable at the console Motor, blower and rectifier of adequate

Progressive, multiple light crescendo indicator. capacity.

Wind indicator light Blower enclosure with soundproof baffle box

Light on Music rack, built - in music rack within console Twenty-five feet of main organ cable to be

Sforzando indicator light supplied, additional cable supplied at

Style # 6 console with roll top with lock \$4.00 per ft., as required to be pulled

and connected by purchaser.

*\* = open f.c.*